

Datasheet

Cube C-02 turnstile





www.oxgard.com info@oxgard.com Tel.+7(812) 366-15-94





1. Basic specifications

Table 1 Basic specifications

Specification	Turnstile	Panel
Overall dimensions(H x W x D), mm:		
-in operating condition	801x801x780	107x107x25
-with fold down arms	281x801x780	
Weight, kg	15	0,5
Temperature range, °C:		
-operation	+1+40	+1+40
-transportation and storage	+1+40	+1+40
Relative humidity, %, no more	80	80
Passage width, mm	500	
Throughput, person/min	30	
Max.number of connected remote	2	
control panels, pcs	2	
Lifetime, years	8	8

Table 2 Electrical specifications

Specification	Turnstile	Panel	
Power supply voltage, V:			
- rated	12.0	12.0	
- working	10.813.2	7.515	
Current type	dire	direct	
Standby average current*, A	0.4		
Average current in a pass mode*, A	0.4		
Maximum absorbed current, A	1.5		

^{*-} values mentioned at a nominal supply voltage



2. Delivery set

Table 3. Delivery set

Denomination	Quantity
Cube C-02 turnstile	
Remote control panel with a cable	1 pc
Cross board unit	1 pc
Wall mount bracket	1 pc
Base Cover	1 pc
Datasheet	1 pc
Installation guidelines	1 pc
Maintenance operations	1 pc
Operational manual	1 pc
Anchor with a screw of MSA8 * type	4 pcs
Screw DIN7991 M8x25*	4 pcs

^{*}optional

The producer reserves the right to change the packaging, specifications and appearance without notice

3. Warranty

3.1. The warranty period is 24 months from the date of sale by the manufacturer, subject to compliance with the requirements for operating conditions in accordance with Installation guidelines and Operation Manual. Date of sale is specified in the data sheet. In case the date of sale is not provided the warranty period is calculated from the date of manufacture of the product indicated in the datasheet and on the product label.

C-02 turnstile 4



- 3.2. Should a problem occur, contact the authorized dealers or the nearest authorized service center. Warranty terms and conditions provide free replacement parts, assemblies, units, etc., in which a manufacturing defect is found. The guarantee is subject to compliance with the requirements of the product maintenance according to Maintenance Operations.
- 3.3. Warranty terms and conditions do not include transport costs and travel to the place of product installation for connecting, configuring, repairing or consulting.
- 3.4. After-sales service will be provided at the rates set by the service center. In the case of non-warranty repair the warranty period for replaced parts and components is 3 months and shall run from the date of shipment of the product to buyer's address.
- 3.5. All claims for quantity, completeness and defects in appearance of the delivered goods are accepted by the manufacturer in writing, no later than five (5) working days of receipt of goods by the customer. In the case of non-compliance with the aforementioned term claims to put the goods on the above terms is not accepted.
- 3.6. Service center has a right to refuse warranty repairs in the following cases:
- the presence of defects that have arisen as a result of violations of the user instructions contained in the installation instructions, owner's manual and maintenance manual:
- when using the product for other purposes;
- if there are signs of change in the user product design;
- the presence of mechanical damage resulting from exposure to fire, shock, or an accident, etc.;
- the presence of mechanical damage resulting from operation of the product in excess of the limits of use and load characteristics declared by the manufacturer;
- the presence of electrical components and parts damaged due to surges, incorrect connections, wrong choice of power supply cable;



- the presence of electrical and other components damaged due to their to exposure to water and other liquids;
- the presence of damages associated with the activity of small animals and insects;
- if there are signs of self-repair out of authorized service center, as well as defects resulting from the use of non-original spare parts;
- if faults have arisen as a result of normal wear and tear or the end of life of parts (consumables, fuses, etc.)

C-02 turnstile



4. Production information

Name	Cube C-02
Serial number	
Production date	
Firmware version of motherboard	
Software version	

5. The certificate of acceptance QCD

Controller	
Signature	
QCD label	



6. Sale information

Seller	
Buyer	
Sale date	
Seller signature and stamp	
Buyer stamp	

7. Installation information

Contractor	
Date of installation	
Name and signature of contractor	
Buyer signature	

C-02 turnstile







PRODUCT IS CERTIFIED

Voltage: 12V DC Current: 5A

Importer: VZR System OU Tulika 19, Tallinn 10613

+ 372 5844 4957

e-mail:

info@vzrsystem.ee www.vzrsystem.ee

Manufacturer:
«Vozrozhdenie»
66, Sofiyskaya str. 192289
St. Petersburg, Russia
Tel. 8(812)706-95-31
e-mail: sales@oxgard.com
www.oxgard.com







OOO "Vozrozhdenie" 66,
Sofiyskaya str.,
192289, Saint-Petersburg
tel./fax + 7 (812) 336 15 94
www.oxgard.com
info@oxgard.com

